

TMATIC®

FLEXIBLE WELDING CABLE

- ▶ VOLTAGE RATING : 0.6 / 1KV
- ▶ OPERATING TEMPERATURE : -30°C ~ 85°C
- ▶ CONDUCTOR : STRANDED BARE COPPER
- ▶ COLOUR : BLACK INSULATION , ORANGE SHEATHING



P/NO	SIZE		MAX. CURRENT RATING (AMP)	APPROX OVERALL DIAMETER (mm)	NO.OF WIRE x WIRE DIA.
	mm ²	AWG			
TM – BWC 35	35	1	300	13.50	1105 x 0.20
TM – BWC 50	50	1/0	400	15.50	1565 x 0.20
TM – BWC 70	70	2/0	500	17.50	2210 x 0.20
TM – BWC 95	95	3/0	600	19.50	2990 x 0.20
TM – BWC 120	120	4/0	700	21.50	3810 x 0.20



P/NO	SIZE		MAX. CURRENT RATING (AMP)	APPROX OVERALL DIAMETER (mm)	NO. OF WIRE x WIRE DIA.
	mm ²	AWG			
TM – OWC 35	35	1	300	13.50	1105 x 0.20
TM – OWC 50	50	1/0	400	15.50	1565 x 0.20
TM – OWC 70	70	2/0	500	17.50	2210 x 0.20
TM – OWC 95	95	3/0	600	19.50	2990 x 0.20
TM – OWC 120	120	4/0	700	21.50	3810 x 0.20



ABRAWELD (S) PTE LTD

No. 1 Upper Aljunied Link , Blk A , #08-06 Joo Seng Warehouse, Singapore 367901
 Tel : +65 68586841 Fax : +65 68586842 email : enquiry@abraweld.com.sg